(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



. | 1980 | Entre of State Color (1981) | Estat Colo

(43) International Publication Date 13 January 2005 (13.01.2005)

PCT

(10) International Publication Number WO 2005/002761 A1

(51) International Patent Classification7:

B22D 18/04

(21) International Application Number:

PCT/IT2003/000579

(22) International Filing Date:

29 September 2003 (29.09.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: BS2003A000068


7 July 2003 (07.07.2003) IT

- (71) Applicant (for all designated States except US): MECCA-NICA BASSI S.P.A. [IT/IT]; Via Triumplina 83, I-25123 Brescia (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): BASSI, Bruno [IT/IT]; Via Panoramica 18, I-25128 Brescia (IT).

- (74) Agents: CRIPPA, Paolo, Ernesto et al.; Jacobacci & Partners S.p.A., Piazzale Arnaldo 2, I-25121 Brescia (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT (utility model), PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: BENCH, MOLD AND CASTING PROCEDURE, IN PARTICULAR FOR ENGINE CYLINDERS HEADS



(57) Abstract: This invention regards a bench (1,16, 17, 29, 30, 31), a mold and a casting procedure, particularly for engine cylinders heads, characterised by a low-pressure casting, that is the introduction of molten metal from a furnace (32) into a mold positioned above it by exercising pressure on the surface of the molten metal inside the same furnace, combined with a gravity feeding of the same mold. Gravity casting takes place with open risers created in the mold, the latter being sealed at the top, at least at the level of these risers, by lids moved by a tilting arm joined to the casting bench.

WO 2005/002761 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.